

Date : 2019/08/28

Shenzhen Century Cloud Core
Technologies Limited
Yabian Community, Shajing Town
Baoan District, Shenzhen, 518104
China
Attn: Shan Xu

Re. : CU US + Canada Certificate

Type of Equipment : SWITCHING POWER SUPPLY
Model Designation : See Certificate
Certificate No. : CU 72182081 0003
File No. : 50170084 003
Engineer/Contact : Sven-Olaf Steinke
Standard(s) : UL 60950-1:2007 R10.14
CAN/CSA-C22.2 NO.60950-1-07+A1:2011+A2:2014

Dear Mr. Xu,

The above referenced technical equipment has been tested and was found to be in compliance with the listed test requirement(s). Enclosed, please find the TUV Rheinland approval document No. CU 72182081 0003. It authorizes you to label the listed product(s) with the TUV Rheinland Mark identified in the approval document. For compliance, the Test Mark must be on the approved unit.

Your product is subject to regular factory follow-up inspections as well as annual certificate and factory registration fees.

In using the TUV Rheinland Mark you are obligated to comply with the TUV Rheinland of North America Service Agreement.

If we can be of any further assistance to you, please do not hesitate to contact us.

Sincerely yours,
Certification Body

Dipl.-Ing. Univ. S. O. Steinke
QA Certification Officer

Enclosure

Certificate



Certificate no.

CU 72182081 03

License Holder:

Shenzhen Century Cloud Core
Technologies Limited
F1-F5, B1 Complex Building
Gangtou Industrial Park
Yabian Community, Shajing Town
Baoan District, Shenzhen, 518104
China

Manufacturing Plant:

ENHANCE ELECTRONICS
CO., LTD. (DONGGUAN)
No.1, Xingye Road,
Fenggang, Fenggang Town,
Dongguan City, Guangdong Province,
China

Test report no.: USA-SS 50170084 003

Client Reference: Xu Shan

Tested to:

UL 60950-1:2007 R10.14
CAN/CSA-C22.2 NO.60950-1-07+A1:2011+A2:2014

Certified Product: SWITCHING POWER SUPPLY

License Fee - Units

Model Designation: APW9+
Rating : (200-240V~, 50/60Hz, 10A) x 2
Output Voltage : 1) DC 14.5-21V; 2) DC 12.3V
Output Current) : 1) 170A; 2) 12A
Protection Class : I
Max. Ambient Temperature : 50°C
Max. Altitude during operation : 2000m

7

Appendix: 1, 1-14

7

Licensed Test mark:

Date of Issue

(day/mo/yr)

28/08/2019

