

Date : 2020/09/28

Shenzhen Guiji Yanghang Technology  
Co., Ltd  
Shajing street, Bao'an District,  
Shenzhen Guangdong  
P.R. China  
Attn: Peng Yurong

**Re. : CU US + Canada Certificate**

Type of Equipment : SERVER  
Model Designation : See Certificate  
Certificate No. : CU 72203688 0001  
File No. : 60407765 001  
Engineer/Contact : Sven-Olaf Steinke  
Standard(s) : UL 62368-1:2014  
CAN/CSA-C22.2 NO. 62368-1-14

Dear Madame or Sir,

The above referenced technical equipment has been tested and was found to be in compliance with the listed test requirement(s). Enclosed, please find the TUV Rheinland approval document No. CU 72203688 0001. It authorizes you to label the listed product(s) with the TUV Rheinland Mark identified in the approval document. For compliance, the Test Mark must be on the approved unit.

Your product is subject to regular factory follow-up inspections as well as annual certificate and factory registration fees.

In using the TUV Rheinland Mark you are obligated to comply with the TUV Rheinland of North America Service Agreement.

If we can be of any further assistance to you, please do not hesitate to contact us.

Sincerely yours,  
Certification Body

Dipl.-Ing. Univ. S. O. Steinke  
QA Certification Officer

Enclosure

# Certificate



Certificate no.

CU 72203688 01

**License Holder:**

Shenzhen Guiji Yanghang Technology Co., Ltd  
217, haosan business building,  
Minzhu Avenue, Minzhu community,  
Shajing street, Bao'an District,  
Shenzhen Guangdong  
P.R. China

**Manufacturing Plant:**

Shenzhen haiyuda Electronic Technology Co., Ltd  
B1 Building, Xinhontai Industrial Zone,  
No. 14, Jian'an Road, Tangwei Village,  
Fuyong Street, Bao'an District,  
518103 Shenzhen City, Guangdong  
P.R. China

**Test report no.:** USA-SOS 60407765 001

**Client Reference:** P . Y .

**Tested to:** UL 62368-1:2014  
CAN/CSA-C22.2 NO. 62368-1-14

**Certified Product:** SERVER

**License Fee - Units**

Model Designation: 240-Ca

7

Rated Voltage : (200-240VAC; 50/60Hz) x 2  
Rated Current : 10A x 2  
Protection Class : I  
Max. Ambient Temperature: 40°C  
Max. Altitude during operation: 2000m

7

Appendix: 1, 1-4

**Licensed Test mark:**



**Date of Issue**

**(day/mo/yr)**

28/09/2020